



SOLVENT BASED RESIN TUNASMINO AMINO

TUNASMINO PRODUCT CODE	SOLVENT	ТҮРЕ	SPECIFICATION									
			Solids Content (%)	Acid Value mg KOH/g (max)	Viscosity (25°C) Pra Tube No.	Colour Gardner (max)	PERFORMANCE	APPLICATION				
UREA FORMALDEHYDE (UF) RESIN												
211-60	n-BA/ Xylene	<i>iso</i> -Butylated UF	60 ± 2	max 5	60% 16 – 17	1	Good hardness, good adhesion, fast dry	Primer and sealer				
215-60	n-BA/ Xylene	<i>n</i> -Butylated UF	60 ± 2	2 – 5	60% 9 – 11	1	Low cure temperature, good adhesion, flexibility, good compatibility with epoxy resin	Low cure baking enamel for metal undercoat				
urea melamine	FORMALDE	hyde (umf) re:	SIN									
221-60	IBA/ Xylene	<i>iso</i> -Butylated UMF	60 ± 2	max 1	60% 16 – 17	1	High viscosity, good hardness, good adhesion	Acid curing, baking enamel				
222-60	IBA/ Xylene	<i>iso</i> -Butylated UMF	60 ± 2	max 2	60% 16 – 17	1	Low odour, good gloss, excellent toughness, good hardness, adhesion, stability	Acid curing for wood and rattan				
222-65	IBA/ Xylene	<i>iso</i> -Butylated UMF	65 ± 2	max 2	65% 18 – 20	1	Low odour, good gloss, excellent toughness, good hardness, adhesion, stability	Acid curing for wood and rattan				
223-65	IBA/ Xylene	<i>iso</i> -Butylated UMF	65 ± 2	max 2	60% 18 – 20	1	Fast dry, high viscosity, low odour, excellent toughness, good hardness, good adhesion	Acid curing sanding sealer				
224-60	IBA/ Xylene	<i>iso</i> -Butylated UMF	60 ± 2	max 2	60% 16 – 17	1	Low odour, good gloss, excellent toughness, good hardness, good adhesion, good stability	Acid curing, baking enamel				
224-60 HV	IBA/ Xylene	<i>iso</i> -Butylated UMF	60 ± 2	max 2	60% 18 – 20	1	Low odour, good gloss, excellent toughness, good hardness, good adhesion, good stability	Acid curing, baking enamel				
230-60	NBA/ Xylene	<i>n</i> -Butylated UMF	60 ± 2	max 1	60% 15 – 16	1	Excellent gloss, good film built, good adhesion, tough & flexible, good stability	Acid curing, baking enamel				





TUNASMINO AMINO (Cont.)

TUNASMINO PRODUCT CODE	SOLVENT	ТҮРЕ	SPECIFICATION							
			Solids Content	Acid Value mg KOH/g	Viscosity (25°C)	Colour Gardner	PERFORMANCE	APPLICATION		
			(%)	(max)	Pra Tube No.	(max)				
MELAMINE FORMALDEHYDE (MF) RESIN										
240-60	IBA/ Xylene	<i>iso</i> -Butylated UMF	60 ± 2	max 2	60% 11 – 13	1	Excellent gloss, good hardness, chemical resistance, water resistance	Acid curing, baking enamel		
BENZOGUANAMINE FORMALDEHYDE (BF) RESIN										
260-55	NBA/ Xylene	<i>n</i> -Butylated BF	55 ± 2	max 1	55% max 1	1	Excellent chemical resistance, excellent flexibility, good hardness, excellent toughness, low viscosity	Baking enamel for can		