



## WATER BASED RESIN

### TUNASSOL LATEX – COATING APPLICATION

TUNASSOL PRODUCT CODE	POLYMER TYPE	SPECIFICATION				PERFORMANCE	APPLICATION
		Solids Content (%)	Viscosity (30°C), cPs	pH	Appearance		
5201	Vinyl Acrylic	58 ± 1	1,500 - 3,000 LVT 4/60	4 - 5	Milky White	Excellent scrub and alkali resistance, good flow and levelling	Interior and exterior decorative paint
5204 C	Vinyl Acrylic	58 ± 1	1,500 - 3,000 LVT 4/60	4 - 5	Milky White	Excellent scrub and alkali resistance, good flow and levelling, good dust/coal binding	Interior and exterior decorative paint, dust/coal suppression
5207	Vinyl Acrylic	57 ± 1	1,000 - 2,500 LVT 4/60	4 - 5	Milky White	Ecogreen paint, excellent scrub and alkali resistance and high pigment loading,	Interior and exterior decorative paint
5208	Vinyl Acrylic	57 ± 1	1,000 - 2,500 LVT 4/60	4 - 5	Milky White	Excellent scrub and alkali resistance and high pigment loading	Interior and exterior decorative paint
5213	Vinyl Acrylic	58 ± 1	4,000 - 6,000 LVT 4/60	4 - 5	Milky White	Good scrub resistance and high pigment loading	Interior and exterior decorative paint
5229	Vinyl Acrylic	59 ± 1	3,000 - 5,000 LVT 4/60	4 - 5	Milky White	Excellent scrub and alkali resistance and high pigment loading, high gloss	Interior and exterior decorative paint
5301 B	Vinyl Veova	50 ± 1	50 - 400 LVT 2/60	4 - 5	Milky White	High scrub and alkali resistance, high pigment loading and excellent durability	Interior and exterior decorative paint
5302	Vinyl Veova	50 ± 1	1,000 - 2,500 LVT 4/60	4 - 5	Milky White	High gloss, scrub and alkali resistance, high pigment loading and excellent durability	Interior and exterior decorative paint



## TUNASSOL LATEX – COATING APPLICATION (Cont.)

TUNASSOL PRODUCT CODE	POLYMER TYPE	SPECIFICATION				PERFORMANCE	APPLICATION
		Solids Content (%)	Viscosity (30°C), cPs	pH	Appearance		
5319	Vinyl Veova	51 ± 1	100 - 500 LVT 2/60	4 - 5	Milky White	Eco green paint, high scrub and alkali resistance and excellent durability	Interior and exterior decorative paint
5334	Vinyl Veova	56 ± 1	2,000 - 4,000 LVT 4/60	4 - 5	Milky White	High scrub and alkali resistance, high pigment loading and excellent durability	Interior and exterior decorative paint
5401	Styrene Acrylic	50 ± 1	2,500 - 5,000 RVT 4/20	8 - 9	Milky White	High PVC for interior decorative paint	Interior and exterior decorative paint
5402	Styrene Acrylic	46 ± 1	Max 100 LVT 1/60	8 - 9	Milky White	Good colour development and gloss	Interior and exterior decorative paint
5417 A	Styrene Acrylic	50 ± 1	4,000 - 8,000 LVT 4/60	7.5 - 8.5	Milky White	High scrub and alkali resistance, low water absorption and flexible film	Interior and exterior decorative paint, waterproofing
5450 A	Styrene Acrylic	52 ± 1	2,000 - 6,000 LVT 4/60	6 - 8	Milky White	High scrub and alkali resistance, low water absorption and flexible film	Interior and exterior decorative paint, waterproofing
5455 A	Styrene Acrylic	50 ± 1	2,000 - 6,000 LVT 4/60	7.5 - 8.5	Milky White	High scrub and alkali resistance, low water absorption and flexible film	Interior and exterior decorative paint, waterproofing
5512 B	All Acrylic	50 ± 1	50 - 300 LVT 2/60	7.5 - 8.5	Milky White	High scrub and alkali resistance, high pigment loading and excellent durability	Interior and exterior decorative paint
5513	All Acrylic	50 ± 1	2,000 - 4,000 LVT 4/60	8.5 - 10	Milky White	High scrub and alkali resistance, high pigment loading and excellent durability	Interior and exterior decorative paint
5518	All Acrylic	40 ± 1	Max 100 LVT 1/6	8 - 9	Milky White	Fast drying, Good dry film clarity, hard and excellent sandability. Good water resistance.	Wood coating - primer and topcoat